## CHBE320 LECTURE V LAPLACE TRANSFORM AND TRANSFER FUNCTION

## **Professor Dae Ryook Yang**


## Fall 2021 Dept. of Chemical and Biological Engineering **Korea University**

**CHBE320 Process Dynamics and Control** 

Korea University 5-1

## Road Map of the Lecture V

- Laplace Transform and Transfer functions
  - Definition of Laplace transform
  - Properties of Laplace transform
  - Inverse Laplace transform
  - Definition of transfer function
  - How to get the transfer functions
  - Properties of transfer function



**CHBE320 Process Dynamics and Control** 

#### SOLUTION OF LINEAR ODE

- 1st-order linear ODE
  - Integrating factor: For  $\frac{dx}{dt} + a(t)x = f(t)$ , I.F. =  $\exp(\int a(t)dt)$  $[xe^{\int a(t)dt}]' = f(t)e^{\int a(t)dt}$   $\longrightarrow x(t) = [\int f(t)e^{\int a(t)dt} dt + C]e^{-\int a(t)dt}$
- High-order linear ODE with constant coeffs.
  - Modes: roots of characteristic equation

For 
$$a_2x'' + a_1x' + a_0x = f(t)$$
, 
$$a_2p^2 + a_1p + a_0 = a_2(p - p_1)(p - p_2) = 0$$

- Depending on the roots, modes are
  - Distinct roots: (e<sup>-p<sub>1</sub>t</sup>, e<sup>-p<sub>2</sub>t</sup>)
     Double roots: (e<sup>-p<sub>1</sub>t</sup>, te<sup>-p<sub>1</sub>t</sup>)
  - Imaginary roots:  $(e^{-\alpha t} \cos \beta t, e^{-\alpha} \sin \beta t)$

Solution is a linear combination of modes and the coefficients are decided by the initial conditions.


· Many other techniques for different cases

**CHBE320 Process Dynamics and Control** 

Korea University 5-3

## LAPLACE TRANSFORM FOR LINEAR ODE AND PDE

- Laplace Transform
  - Not in time domain, rather in frequency domain
  - Derivatives and integral become some operators.
  - ODE is converted into algebraic equation
  - PDE is converted into ODE in spatial coordinate
  - Need inverse transform to recover time-domain solution



CHBE320 Process Dynamics and Control

Korea University

5-4

### **DEFINITION OF LAPLACE TRANSFORM**

Definition

$$F(s) = \mathfrak{L}{f(t)} \triangleq \int_0^\infty f(t)e^{-s} dt$$

- $\overline{F(s)}$  is called Laplace transform of f(t).
- f(t) must be piecewise continuous.
- F(s) contains no information on f(t) for t < 0.
- The past information on f(t) (for t < 0) is irrelevant.
- The s is a complex variable called "Laplace transform variable"
- Inverse Laplace transform

$$f(t) = \mathfrak{L}^{-1}\{F(s)\}$$

-  $\mathfrak{L}$  and  $\mathfrak{L}^{-1}$  are linear.  $\mathfrak{L}\{af_1(t) + bf_2(t)\} = aF_1(s) + bF_2(s)$ 

**CHBE320 Process Dynamics and Control** 


Korea University 5

5-5

#### LAPLACE TRANSFORM OF FUNCTIONS

• Constant function, a

$$\mathfrak{L}{a} = \int_0^\infty ae^{-st} dt = -\frac{a}{s}e^{-st}\Big|_0^\infty = 0 - \left(-\frac{a}{s}\right) = \frac{a}{s}$$



• Step function, S(t)


$$f(t) = S(t) = \begin{cases} 1 & \text{for } t \ge 0 \\ 0 & \text{for } t < 0 \end{cases}$$

$$\mathfrak{L}\{S(t)\} = \int_{0}^{\infty} e^{-st} dt = -\frac{1}{s} e^{-st} \bigg|_{0}^{\infty} = 0 - \left(-\frac{1}{s}\right) = \frac{1}{s}$$



• Exponential function, e-bt


$$\mathfrak{Q}\{e^{-bt}\} = \int_0^\infty e^{-bt} e^{-st} dt = \frac{-1}{s+b} e^{-(b+s)t} \bigg|_0^\infty = \frac{1}{s+b}$$



CHBE320 Process Dynamics and Control

## Trigonometric functions

- **Euler's Identity:** 
$$e^{j\omega t} \triangleq \cos \omega t + j \sin \omega t$$
  
 $\cos \omega t = \frac{1}{2} (e^{j\omega t} + e^{-j\omega})$   $\sin \omega t = \frac{1}{2j} (e^{j\omega t} - e^{-j\omega})$ 




$$\mathfrak{L}\{\sin\omega\,t\} = \mathfrak{L}\left\{\frac{1}{2j}e^{j\omega t}\right\} - \mathfrak{L}\left\{\frac{1}{2j}e^{-j\omega t}\right\} = \frac{1}{2j}\left(\frac{1}{s-j\omega} - \frac{1}{s+j\omega}\right) = \frac{\omega}{s^2 + \omega^2}$$

$$\mathfrak{L}\{\cos\omega\,t\} = \mathfrak{L}\left\{\frac{1}{2}e^{j\omega t}\right\} + \mathfrak{L}\left\{\frac{1}{2}e^{-j\omega t}\right\} = \frac{1}{2}\left(\frac{1}{s-j\omega} + \frac{1}{s+j\omega}\right) = \frac{s}{s^2+\omega^2}$$

• Rectangular pulse, P(t)

$$f(t) = P(t) = \begin{cases} 0 & \text{for } t > t_w \\ h & \text{for } t_w \ge t \ge 0 \\ 0 & \text{for } t < 0 \end{cases}$$

$$\mathfrak{L}\{P(t)\} = \int_0^{t_w} h e^{-st} dt = -\frac{h}{s} e^{-st} \bigg|_0^{t_w} = \frac{h}{s} (1 - e^{-t_w s})$$



CHBE320 Process Dynamics and Control

Korea University

#### • Impulse function, $\delta(t)$

$$f(t) = \delta(t) = \lim_{t_w \to 0} \begin{cases} 0 & \text{for } t > t_w \\ 1/t_w & \text{for } t_w \ge t \ge 0 \\ 0 & \text{for } t < 0 \end{cases}$$

$$\begin{array}{c|c} f(t) \\ \hline 1/t_w \\ \hline \\ t_w \\ t \end{array}$$


$$\mathfrak{L}\{\delta(t)\} = \lim_{t_w \to 0} \int_0^{t_w} \frac{1}{t_w} e^{-st} dt = \lim_{t_w \to 0} \frac{1}{t_w s} (1 - e^{-t_w s}) = 1$$

$$\left(\text{L'Hospital's rule: } \lim_{t \to 0} \frac{f(t)}{g(t)} = \lim_{t \to 0} \frac{f'(t)}{g'(t)}\right)$$

#### Ramp function, t


# $\mathfrak{L}{t} = \int_0^\infty t e^{-st} dt$ $= \frac{t}{-s} e^{-st} \Big|_0^\infty - \int_0^\infty \frac{e^{-st}}{-s} dt = \frac{1}{s} \int_0^\infty e^{-st} dt = \frac{1}{s^2}$

(Integration by part:  $\int_{0}^{\infty} f' \cdot g dt = f \cdot g \Big|_{0}^{\infty} - \int_{0}^{\infty} f \cdot g' dt$ )



#### Refer the Table 3.1 (Seborg et al.) for other functions


**CHBE320 Process Dynamics and Control** 



**CHBE320 Process Dynamics and Control** 

**Korea University** 

5-9



CHBE320 Process Dynamics and Control

Korea University 5-10

#### PROPERTIES OF LAPLACE TRANSFORM

#### Differentiation

$$\mathfrak{L}\left\{\frac{df}{dt}\right\} = \int_0^\infty f' \cdot e^{-s} \ dt = f(t)e^{-st}\Big|_0^\infty - \int_0^\infty f \cdot (-s)e^{-st} dt \qquad \text{(by } i.b.p.)$$

$$= s \int_0^\infty f \cdot e^{-s} \ dt - f(0) = sF(s) - f(0)$$

$$\mathfrak{L}\left\{\frac{d^2f}{dt^2}\right\} = \int_0^\infty f'' \cdot e^{-st} dt = f(t)'e^{-s} \Big|_0^\infty - \int_0^\infty f' \cdot (-s)e^{-s} dt = s \int_0^\infty f' \cdot e^{-st} dt - f'(0)$$

$$= s(sF(s) - f(0)) - f'(0) = s^2F(s) - sf(0) - f'(0)$$

$$\begin{split} \mathfrak{L}\left\{ &\frac{d^{n}f}{dt^{n}} \right\} = \int_{0}^{\infty} f^{(n)} \cdot e^{-st} dt = f(t)^{(n-1)} e^{-s} \Big|_{0}^{\infty} - \int_{0}^{\infty} f^{(n-1)} \cdot (-s) e^{-st} dt \\ &= s \int_{0}^{\infty} f^{(n-1)} \cdot e^{-st} dt - f^{(n-1)}(0) = s \left( \mathfrak{L}\left\{ \frac{d^{n-1}f}{dt^{n-1}} \right\} \right) - f^{(n-1)}(0) \\ &= s^{n}F(s) - s^{n-1}f(0) - \dots - sf^{(n-2)}(0) - f^{(n-1)}(0) \end{split}$$

CHBE320 Process Dynamics and Control

Korea University 5-11

- If  $f(0) = f'(0) = f''(0) = \dots = f^{(n-1)}(0) = 0$ ,  $g\left\{\frac{df}{dt}\right\} = sF(s)$ 
  - Initial condition effects are vanished.
  - It is very convenient to use deviation variables so that all the effects of initial condition vanish.

$$\mathfrak{L}\left\{\frac{df}{dt}\right\} = sF(s)$$

$$\mathfrak{L}\left\{\frac{d^2f}{dt^2}\right\} = s^2F(s)$$

$$\vdots$$

$$\mathfrak{L}\left\{\frac{d^n f}{dt^n}\right\} = s^n F(s)$$

## · Transforms of linear differential equations.

$$y(t) \xrightarrow{\varrho} Y(s), \qquad u(t) \xrightarrow{\varrho} U(s)$$

$$\frac{dy(t)}{dt} \xrightarrow{\varrho} sY(s) \quad (\text{if } y(0) = 0)$$

$$\tau \frac{dy(t)}{dt} = -y(t) + Ku(t) \ (y(0) = 0) \xrightarrow{\mathfrak{L}} (\tau s + 1)Y(s) = KU(s)$$

$$\frac{\partial T_L}{\partial t} = -v \frac{\partial T_L}{\partial z} + \frac{1}{\tau_{tv}} (T_w - T_L) \xrightarrow{\mathfrak{L}} \tau_{HL} v \frac{\partial \tilde{T}_L(s)}{\partial z} + (\tau_{HL} s + 1) \tilde{T}_L(s) = \tilde{T}_w(s)$$


**CHBE320 Process Dynamics and Control** 

Integration

$$\mathfrak{L}\left\{\int_{0}^{t} f(\xi)d\xi\right\} = \int_{0}^{\infty} \left(\int_{0}^{t} f(\xi)d\xi\right) e^{-st}dt$$

$$= \frac{e^{-st}}{-s} \int_{0}^{t} f(\xi)d\xi \int_{0}^{\infty} \mathbf{f} \cdot \mathbf{$$

• Time delay (Translation in time)



· Derivative of Laplace transform

$$\frac{dF(s)}{ds} = \frac{d}{ds} \int_0^\infty f \cdot e^{-st} dt = \int_0^\infty f \cdot \frac{d}{ds} e^{-st} dt = \int_0^\infty (-t \cdot f) e^{-st} dt = \mathfrak{L}[-t \cdot f(t)]$$

**CHBE320 Process Dynamics and Control** 

Korea University 5-13

#### Final value theorem

- From the LT of differentiation, as s approaches to zero

$$\lim_{s \to 0} \int_0^\infty \frac{df}{dt} \cdot e^{-s} dt = \int_0^\infty \frac{df}{dt} \cdot \lim_{s \to 0} e^{-s} dt = \lim_{s \to 0} [sF(s) - f(0)]$$

$$\int_0^\infty \frac{df}{dt} dt = f(\infty) - f(0) = \lim_{s \to 0} sF(s) - f(0) \Rightarrow f(\infty) = \lim_{s \to 0} sF(s)$$

- Limitation:  $f(\infty)$  has to exist. If it diverges or oscillates, this theorem is not valid.

#### Initial value theorem


- From the LT of differentiation, as s approaches to infinity

$$\lim_{s \to \infty} \int_0^\infty \frac{df}{dt} \cdot e^{-s} dt = \lim_{s \to \infty} [sF(s) - f(0)]$$

$$\lim_{s \to \infty} \int_0^\infty \frac{df}{dt} e^{-st} dt = 0 = \lim_{s \to \infty} sF(s) - f(0) \Rightarrow f(0) = \lim_{s \to \infty} sF(s)$$

CHBE320 Process Dynamics and Control

## **EXAMPLE ON LAPLACE TRANSFORM (1)**



$$f(t) = \begin{cases} 1.5t & \text{for } 0 \le t < 2\\ 3 & \text{for } 2 \le t < 6\\ 0 & \text{for } 6 \le t\\ 0 & \text{for } t < 0 \end{cases}$$

$$f(t) = 1.5t \,S(t) - 1.5(t-2) \,S(t-2) - 3 \,S(t-6)$$

$$\therefore F(s) = \mathfrak{L}\{f(t)\} = \frac{1.5}{s^2} (1 - e^{-2s}) - \frac{3}{s} e^{-6s}$$

- For  $F(s) = \frac{2}{s-5}$ , find f(0) and  $f(\infty)$ .
  - Using the initial and final value theorems

$$f(0) = \lim_{s \to \infty} s F(s) = \lim_{s \to \infty} \frac{2s}{s - 5} = 2s$$

$$f(0) = \lim_{s \to \infty} s F(s) = \lim_{s \to \infty} \frac{2s}{s - 5} = 2 \qquad f(\infty) = \lim_{s \to 0} s F(s) = \lim_{s \to 0} \frac{2s}{s - 5} = 0$$

- But the final value theorem is not valid because

$$\lim_{t \to \infty} f(t) = \lim_{t \to \infty} 2 e^{5t}$$

CHBE320 Process=Dynamics and Control

Korea University 5-15

## **EXAMPLE ON LAPLACE TRANSFORM (2)**

· What is the final value of the following system?

$$x'' + x' + x = \sin t$$
;  $x(0) = x'(0) = 0$ 

$$\Rightarrow s^{2}X(s) + sX(s) + X = \frac{1}{s^{2} + 1} \Rightarrow x(s) = \frac{1}{(s^{2} + 1)(s^{2} + s + 1)}$$

$$\chi(\infty) = \lim_{s \to 0} \frac{s}{(s^2 + 1)(s^2 + s + 1)} = 0$$

- Actually,  $\chi(\infty)$  cannot be defined due to sin t term.
- Find the Laplace transform for  $(t \sin \omega t)$  ?

From 
$$\frac{dF(s)}{ds} = \mathfrak{L}[-t \cdot f(t)]$$

$$\mathfrak{L}[t \cdot \sin \omega \, t] = -\frac{d}{ds} \left[ \frac{\omega}{s^2 + \omega^2} \right] = \frac{2\omega s}{(s^2 + \omega^2)^2}$$

**CHBE320 Process Dynamics and Control** 

#### INVERSE LAPLACE TRANSFORM

Used to recover the solution in time domain

$$\mathfrak{L}^{-1}\{F(s)\} = f(t)$$

- From the table
- By partial fraction expansion
- By inversion using contour integral

$$f(t) = \mathfrak{L}^{-1}{F(s)} = \frac{1}{2\pi i} \oint_C e^{st} F(s) ds$$

#### Partial fraction expansion

 After the partial fraction expansion, it requires to know some simple formula of inverse Laplace transform such as

$$\frac{1}{(\tau s+1)}, \frac{s}{(s+b)^2 + \omega^2}, \frac{(n-1)!}{s^n}, \frac{e^{-\theta}}{\tau^2 s^2 + 2\zeta \tau s + 1}, \text{ etc.}$$

**CHBE320 Process Dynamics and Control** 

Korea University 5-17

#### PARTIAL FRACTION EXPANSION

$$F(s) = \frac{N(s)}{D(s)} = \frac{N(s)}{(s+p_1)\cdots(s+p_n)} = \frac{\alpha_1}{(s+p_1)} + \dots + \frac{\alpha_n}{(s+p_n)}$$

- Case I: All  $p_i$ 's are distinct and real
  - By a root-finding technique, find all roots (time-consuming)
  - Find the coefficients for each fraction
    - Comparison of the coefficients after multiplying the denominator
    - Replace some values for s and solve linear algebraic equation
    - Use of Heaviside expansion
      - Multiply both side by a factor,  $(s+p_i)$ , and replace s with  $-p_i$ .

$$\alpha_i = (s + p_i) \frac{N(s)}{D(s)} \bigg|_{s = -p_i}$$

- Inverse LT

$$f(t) = \alpha_1 e^{-p_1 t} + \alpha_2 e^{-p_2 t} + \dots + \alpha_n e^{-p_n t}$$

CHBE320 Process Dynamics and Control

## · Case II: Some roots are repeated

$$F(s) = \frac{N(s)}{D(s)} = \frac{N(s)}{(s+p)^r} = \frac{b_{r-1}s^{r-1} + \dots + b_0}{(s+p)^r} = \frac{\alpha_1}{(s+p)} + \dots + \frac{\alpha_r}{(s+p)^r}$$

- Each repeated factors have to be separated first.
- Same methods as Case I can be applied.
- Heaviside expansion for repeated factors

$$\alpha_{r-i} = \frac{1}{i!} \frac{d^{(i)}}{ds^{(i)}} \left( \frac{N(s)}{D(s)} (s+p)^r \right) \bigg|_{s=-p} \quad (i=0,\cdots,r-1)$$

- Inverse LT

$$f(t) = \alpha_1 e^{-p} + \alpha_2 t e^{-pt} + \dots + \frac{\alpha_r}{(r-1)!} t^{r-1} e^{-p}$$

**CHBE320 Process Dynamics and Control** 

Korea University 5-19

## Case III: Some roots are complex

$$F(s) = \frac{N(s)}{D(s)} = \frac{c_1 s + c_0}{s^2 + d_1 s + d_0} = \frac{\alpha_1 (s+b) + \beta_1 \omega}{(s+b)^2 + \omega^2}$$

- Each repeated factors have to be separated first.
- Then,

$$\frac{\alpha_1(s+b) + \beta_1 \omega}{(s+b)^2 + \omega^2} = \alpha_1 \frac{(s+b)}{(s+b)^2 + \omega^2} + \beta_1 \frac{\omega}{(s+b)^2 + \omega^2}$$

where 
$$b=d_1/2$$
,  $\omega=\sqrt{{d_0-{d_1}^2/4}}$   $\alpha_1=c_1$ ,  $\beta_1=(c_0-\alpha_1b)/\omega$ 

- Inverse LT

$$f(t) = \alpha_1 e^{-bt} \cos \omega t + \beta_1 e^{-bt} \sin \omega t$$

CHBE320 Process Dynamics and Control

## EXAMPLES ON INVERSE LAPLACE TRANSFORM

• 
$$F(s) = \frac{(s+5)}{s(s+1)(s+2)(s+3)} = \frac{A}{s} + \frac{B}{s+1} + \frac{C}{s+2} + \frac{D}{s+3}$$
 (distinct)

- Multiply each factor and insert the zero value

$$\begin{split} \frac{(s+5)}{(s+1)(s+2)(s+3)}\bigg|_{s=0} &= \left(A+s\frac{B}{s+1}+s\frac{C}{s+2}+s\frac{D}{s+3}\right)\bigg|_{s=0} \Rightarrow A=5/6 \\ \frac{(s+5)}{s(s+2)(s+3)}\bigg|_{s=-1} &= \left(\frac{A(s+1)}{s}+B+\frac{C(s+1)}{s+2}+\frac{D(s+1)}{s+3}\right)\bigg|_{s=-1} \Rightarrow B=-2 \\ \frac{(s+5)}{s(s+1)(s+3)}\bigg|_{s=-2} &= \left(\frac{A(s+2)}{s}+\frac{B(s+2)}{s+1}+C+\frac{D(s+2)}{s+3}\right)\bigg|_{s=-2} \Rightarrow C=3/2 \\ \frac{(s+5)}{s(s+1)(s+2)}\bigg|_{s=-3} &= \left(\frac{A(s+3)}{s}+\frac{B(s+3)}{s+1}+\frac{C(s+3)}{s+2}+D\right)\bigg|_{s=-3} \Rightarrow D=-1/3 \\ \therefore f(t) &= \mathfrak{L}^{-1}\{F(s)\} = \frac{5}{6}-2e^{-t}+\frac{3}{2}e^{-2}-\frac{1}{3}e^{-3} \end{split}$$

**CHBE320 Process Dynamics and Control** 

Korea University 5-21

• 
$$F(s) = \frac{1}{(s+1)^3(s+2)} = \frac{As^2 + Bs + C}{(s+1)^3} + \frac{D}{(s+2)}$$
 (repeated)  

$$1 = (As^2 + Bs + C)(s+2) + D(s+1)^3$$

$$= (A+D)s^3 + (2A+B+3D)s^2 + (2B+C+3D)s + (2C+D)$$

$$\therefore A = -D, \quad 2A+B+3D = 0, \quad 2B+C+3D = 0, \quad 2C+D = 1$$

$$\Rightarrow A = 1, \quad B = 1, \quad C = 1, \quad D = -1$$

$$- \text{ Use of Heaviside expansion} \quad \alpha_{r-i} = \frac{1}{i!} \frac{d^{(i)}}{ds^{(i)}} \left( \frac{N(s)}{D(s)} (s+p)^r \right) \Big|_{s=-p} \quad (i = 0, \dots, r-1)$$

$$\frac{s^2 + s + 1}{(s+1)^3} = \frac{\alpha_1}{(s+1)} + \frac{\alpha_2}{(s+1)^2} + \frac{\alpha_3}{(s+1)^3}$$

$$(i = 0): \alpha_3 = (s^2 + s + 1) \Big|_{s=-1} = 1$$

$$(i = 1): \alpha_2 = \frac{1}{1!} \frac{d}{ds} (s^2 + s + 1) \Big|_{s=-1} = -1$$

$$(i = 2): \alpha_1 = \frac{1}{2!} \frac{d^2}{ds^2} (s^2 + s + 1) \Big|_{s=-1} = 1$$

$$\therefore f(t) = \mathfrak{L}^{-1} \{F(s)\} = e^{-t} - te^{-t} + \frac{1}{2} t^2 e^{-t} - e^{-2t}$$

**CHBE320 Process Dynamics and Control** 

• 
$$F(s) = \frac{(s+1)}{s^2(s^2+4s+5)} = \frac{A(s+2)+B}{(s+2)^2+1} + \frac{Cs+D}{s^2}$$
 (complex)  
 $s+1 = A(s+2)s^2+Bs^2+(Cs+D)(s^2+4s+5)$   
 $= (A+C)s^3+(2A+B+4C+D)s^2+(5C+4D)s+5D$   
 $\therefore A = -C, \quad 2A+B+4C+D = 0, \quad 5C+4D = 1, \quad 5D = 1$   
 $\Rightarrow A = -1/25, \quad B = -7/25, \quad C = 1/25, \quad D = 1/5$   
 $\frac{A(s+2)+B}{(s+2)^2+1} = -\frac{1}{25}\frac{(s+2)}{(s+2)^2+1} - \frac{7}{25}\frac{B}{(s+2)^2+1}$   
 $\frac{Cs+D}{s^2} = \frac{1}{25}\frac{1}{s} + \frac{1}{5}\frac{1}{s^2}$   
 $\therefore f(t) = \mathfrak{L}^{-1}{F(s)} = -\frac{1}{25}e^{-2t}\cos t - \frac{7}{25}e^{-2t}\sin t + \frac{1}{25} + \frac{1}{5}t$ 

**CHBE320 Process Dynamics and Control** 

Korea University 5-23

• 
$$F(s) = \frac{1+e^{-2}}{(4s+1)(3s+1)} = \left(\frac{A}{4s+1} + \frac{B}{3s+1}\right)(1+e^{-2s})$$
 (Time delay)  

$$A = 1/(3s+1)\Big|_{s=-1/4} = 4, \qquad B = 1/(4s+1)\Big|_{s=-1/3} = -3$$

$$\therefore f(t) = \mathfrak{L}^{-1}{F(s)} = \mathfrak{L}^{-1}\left\{\frac{4}{4s+1} - \frac{3}{3s+1}\right\} + \mathfrak{L}^{-1}\left\{\frac{4e^{-2s}}{4s+1} - \frac{3e^{-2}}{3s+1}\right\}$$

$$= e^{-t/4} - e^{-t/3} + \left(e^{-(t-2)/4} - e^{-(t-2)/3}\right)S(t-2)$$



CHBE320 Process Dynamics and Control

#### SOLVING ODE BY LAPLACE TRANSFORM

#### Procedure

- 1. Given linear ODE with initial condition,
- 2. Take Laplace transform and solve for output
- 3. Inverse Laplace transform

• **Example:** Solve for 
$$5\frac{dy}{dt} + 4y = 2$$
;  $y(0) = 1$ 

$$2\left\{5\frac{dy}{dt}\right\} + 2\left\{4y\right\} = 2\left\{2\right\} \implies 5(sY(s) - y(0)) + 4Y(s) = \frac{2}{s}$$

$$(5s + 4)Y(s) = \frac{2}{s} + 5 \implies Y(s) = \frac{5s + 2}{s(5s + 4)}$$

$$\therefore y(t) = 2^{-1}\left\{Y(s)\right\} = 2^{-1}\left\{\frac{0.5}{s} + \frac{2.5}{5s + 4}\right\} = 0.5 + 0.5e^{-0.8t}$$

CHBE320 Process Dynamics and Control

Korea University 5-25

## **TRANSFER FUNCTION (1)**

#### Definition

An algebraic expression for the dynamic relation between the input and output of the process model

$$5\frac{dy}{dt} + 4y = u; \ y(0) = 1$$
Let  $\tilde{y} = y - 1$  and  $\tilde{u} = u - 4$ 

$$(5s + 4)\tilde{Y}(s) = \tilde{U}(s) \Rightarrow \frac{\tilde{Y}(s)}{\tilde{U}(s)} = \frac{1}{5s + 4} = 0.25$$

$$1.25s + 1$$

$$G(s)$$

#### · How to find transfer function

- 1. Find the equilibrium point
- 2. If the system is nonlinear, then linearize around equil. point
- 3. Introduce deviation variables
- 4. Take Laplace transform and solve for output
- 5. Do the Inverse Laplace transform and recover the original variables from deviation variables

CHBE320 Process Dynamics and Control


## **TRANSFER FUNCTION (2)**

#### Benefits

 Once TF is known, the output response to various given inputs can be obtained easily.

$$y(t) = \mathfrak{L}^{-1}{Y(s)} = \mathfrak{L}^{-1}{G(s)U(s)} \neq \mathfrak{L}^{-1}{G(s)}\mathfrak{L}^{-1}{U(s)}$$

- Interconnected system can be analyzed easily.
  - By block diagram algebra



- Easy to analyze the qualitative behavior of a process, such as stability, speed of response, oscillation, etc.
  - · By inspecting "Poles" and "Zeros"
  - Poles: all s's satisfying D(s)=0
  - Zeros: all s's satisfying N(s)=0

CHBE320 Process Dynamics and Control

Korea University 5-27

#### TRANSFER FUNCTION (3)

Steady-state Gain: The ratio between ultimate changes in input and output

Gain=
$$K = \frac{\Delta \text{ouput}}{\Delta \text{input}} = \frac{(y(\infty) - y(0))}{(u(\infty) - u(0))}$$

- For a unit step change in input, the gain is the change in output
- Gain may not be definable: for example, integrating processes and processes with sustaining oscillation in output
- From the final value theorem, unit step change in input with zero initial condition gives

$$K = \frac{y(\infty)}{1} = \lim_{s \to 0} s \, Y(s) = \lim_{s \to 0} s \, G(s) \frac{1}{s} = \lim_{s \to 0} G(s)$$

- The transfer function itself is an impulse response of the system  $Y(s) = G(s)U(s) = G(s)\Re\{\delta(t)\} = G(s)$ 

CHBE320 Process Dynamics and Control

#### **EXAMPLE**

Horizontal cylindrical storage tank (Ex4.7)

$$\frac{dm}{dt} = \rho \frac{dV}{dt} = \rho q_i - \rho q$$

$$V(h) = \int_0^h Lw_i(\tilde{h})d\tilde{h} \Rightarrow \frac{dV}{dt} = Lw_i(h)\frac{dh}{dt}$$

$$w_i(h)/2 = \sqrt{R^2 - (R - h)^2} = \sqrt{(2R - h)h}$$


$$w_i L\frac{dh}{dt} = q_i - q \Rightarrow \frac{dh}{dt} = \frac{1}{2L\sqrt{(D - h)h}}(q_i - q) \text{ (Nonlinear ODE)}$$

- **Equilibrium point:**  $(\bar{q}_i, \bar{q}, \bar{h})$   $0 = (\bar{q}_i \bar{q})/(2L\sqrt{(D \bar{h})\bar{h}})$ (if  $\bar{q}_i = \bar{q}$ ,  $\bar{h}$  can be any value in  $0 \le \bar{h} \le D$ .)
- Linearization:

$$\frac{dh}{dt} = f(h,q_i,q) = \frac{\partial f}{\partial h}\bigg|_{(\bar{h},\bar{q}_i,\bar{q})} (h-\bar{h}) + \frac{\partial f}{\partial q_i}\bigg|_{(\bar{h},\bar{q}_i,\bar{q})} (q_i-\bar{q}_i) + \frac{\partial f}{\partial q}\bigg|_{(\bar{h},\bar{q}_i,\bar{q})} (q-\bar{q})$$

CHBE320 Process Dynamics and Control

Korea University 5-29



- $s\widetilde{H}(s) = k\widetilde{Q}_i(s) k\widetilde{Q}(s)$  Transfer function between  $\widetilde{H}(s)$  and  $\widetilde{Q}(s)$ :  $-\frac{k}{s}$  (integrating)
   Transfer function between  $\widetilde{H}(s)$  and  $\widetilde{Q}_i(s)$ :  $\frac{k}{s}$  (integrating)
- If  $\bar{h}$  is near 0 or D, k becomes very large and  $\bar{h}$  is around D/2, k becomes minimum.
- ⇒ The model could be quite different depending on the operating condition used for the linearization.
- ⇒ The best suitable range for the linearization in this case is around D/2. (less change in gain)
- ⇒ Linearized model would be valid in very narrow range near 0.

**CHBE320 Process Dynamics and Control** 

#### PROPERTIES OF TRANSFER FUNCTION

Additive property

$$Y(s) = Y_1(s) + Y_2(s)$$
  
=  $G_1(s)X_1(s) + G_2(s)X_2(s)$ 



Multiplicative property

$$X_3(s) = G_2(s)X_2(s)$$

$$= G_2(s)[G_1(s)X_1(s)]$$

$$X_3(s)$$

$$G_1(s)$$

$$X_2(s)$$

$$G_2(s)$$

$$X_3(s)$$

- · Physical realizability
  - In a transfer function, the order of numerator(m) is greater than that of denominator(n): called "physically unrealizable"
  - The order of derivative for the input is higher than that of output. (requires future input values for current output)

**CHBE320 Process Dynamics and Control** 


Korea University 5-31

#### **EXAMPLES ON TWO TANK SYSTEM**

• Two tanks in series (Ex3.7)  $C_{\underline{i}}$ 

- No reaction
$$V_1 \frac{dc_1}{dt} + qc_1 = qc_i$$

$$V_2 \frac{dc_2}{dt} + qc_2 = qc_1$$



- Initial condition:  $c_1(0) = c_2(0) = 1 \text{ kg mol/m}^3$  (Use deviation var.)
- Parameters:  $V_1/q=2$  min.,  $V_2/q=1.5$  min.
- Transfer functions


$$\frac{\tilde{C}_1(s)}{\tilde{C}_i(s)} = \frac{1}{(V_1/q)s+1} \qquad \qquad \frac{\tilde{C}_2(s)}{\tilde{C}_1(s)} = \frac{1}{(V_2/q)s+1}$$

$$\frac{\tilde{\mathcal{C}}_2(s)}{\tilde{\mathcal{C}}_i(s)} = \frac{\tilde{\mathcal{C}}_2(s)}{\tilde{\mathcal{C}}_1(s)} \frac{\tilde{\mathcal{C}}_1(s)}{\tilde{\mathcal{C}}_i(s)} = \frac{1}{((V_2/q)s+1)((V_1/q)s+1)}$$

CHBE320 Process Dynamics and Control

## · Pulse input

$$\tilde{C}_i^P(s) = \frac{5}{s}(1 - e^{-0.25s})$$



## · Equivalent impulse input


$$\tilde{C}_i^{\delta}(s) = \mathfrak{L}\{(5 \times 0.25)\delta(t)\} = 1.25$$

### · Pulse response vs. Impulse response

$$\begin{split} \tilde{C}_{1}^{P}(s) &= \frac{1}{2s+1} \tilde{C}_{i}^{P}(s) = \frac{5}{s(2s+1)} (1 - e^{-0.25s}) \\ &= \left(\frac{5}{s} - \frac{10}{2s+1}\right) (1 - e^{-0.25s}) \\ &\Rightarrow \tilde{c}_{1}^{P}(t) = 5(1 - e^{-t/2}) \\ &\quad - 5(1 - e^{-(t-0.25)/2}) S(t - 0.25) \end{split}$$

$$\tilde{C}_{1}^{\delta}(s) &= \frac{1}{2s+1} \tilde{C}_{i}^{\delta}(s) = \frac{1.25}{(2s+1)}$$

$$\Rightarrow \tilde{c}_{1}^{\delta} = 0.625e^{-t/2} \end{split}$$



**CHBE320 Process Dynamics and Control** 

Korea University 5-33

$$\begin{split} \tilde{C}_{2}^{P}(s) &= \frac{1}{(2s+1)(1.5s+1)} \tilde{C}_{i}^{P}(s) = \frac{5}{s(2s+1)(1.5s+1)} (1 - e^{-0.25s}) \\ &= \left(\frac{5}{s} - \frac{40}{2s+1} + \frac{22.5}{1.5s+1}\right) (1 - e^{-0.25s}) \end{split}$$


$$\Rightarrow \overline{c_2^P(t)} = (5 - 20e^{-t/2} + 15e^{-t/1.5}) - (5 - 20e^{-(t-0.25)/2} + 15e^{-(t-0.25)/1.5}) S(t - 0.25)$$

$$\tilde{C}_{2}^{\delta}(s) = \frac{1}{(2s+1)(1.5s+1)} \tilde{C}_{i}^{\delta}(s)$$

$$= \frac{1.25}{(2s+1)(1.5s+1)}$$

$$= \frac{5}{2s+1} - \frac{3.75}{1.5s+1}$$

$$\Rightarrow \tilde{C}_{2}^{\delta} = 2.5e^{-t/2} - 2.5e^{-t/1.5}$$



CHBE320 Process Dynamics and Control

Korea University 5-34